

**4.00 (IN) DRYWALL STUD WITH 1.25 (IN) FLANGE - 33MILS (20GA)
COATING: G40**

Web Depth	4.000 (in)
Flange Width	1.25 (in)
Lip Length	0.281 (in)
Design Thickness	0.0346 (in)
Min. Deliverable Thickness	0.0329 (in)
Punchout Width	1.5 (in)
Punchout Length	4 (in)
Yield Strength, Fy	33 (ksi)

GROSS SECTION PROPERTIES (FULL SECTION)

Area (Ag)	0.2340 (in ²)
Member weight per foot of length	0.7962 (lb/ft)
Moment of inertia X-X axis (Ix)	0.5508 (in ⁴)
Section Modulus X-X axis (Sxx)	0.2754 (in ³)
Radius of gyration X-X Axis (Rx)	1.5342 (in)
Moment of inertia Y-Y axis (Iyy)	0.0433 (in ⁴)
Radius of gyration Y-Y axis (Ry)	0.4299 (in)

EFFECTIVE SECTION PROPERTIES

Moment of inertia for deflection (Ixe)	0.5508 (in ⁴)
Section Modulus (Sxe)	0.2307 (in ³)
Allowable Local Buckling Moment (Ma)	4.56 (in-k)
Allowable Distortional Buckling Moment (Ma-d)	4.37 (in-k)
Allowable shear force in web (Va-g)	976 (lb)
Allowable shear force in web at Punchout (Vanet)	595 (lb)

TORSIONAL PROPERTIES

St. Venant torsional constant (J x 1000)	0.0934 (in ⁴)
Warping Constant (Cw)	0.1391 (in ⁶)
Distance from shear center to neutral axis (Xo)	-0.8006 (in)
Radii of gyration (Ro)	1.7832 (in)
Torsional flexural constant (b)	0.7984

